



BS 100/30/20

Sunscreening



Reynaers' BS (Brise Soleil) systems are designed to provide an aesthetic and efficient shading solution to almost any new and existing building. They are offered both standard or as a bespoke solution. Brise Soleil is the generic term for a system of louvres which, when fitted to the external façade of a building, provides protection against solar heat and glare.

TECHNICAL CHARACTERISTICS



**BS 100
PRE-ASSEMBLED FRAME**



**BS 100
FIXED LOUVRE**



**BS 100
MOVABLE LOUVRE**



**BS 100
GLASS LOUVRE**

Style variants				
Shape louvres	ellipse	ellipse	ellipse	hardened glass
Size louvres	140 mm / 180 mm	from 120 to 400 mm	from 120 to 400 mm	300 x 10 to 12 mm
(Fixed) angle	45°	0°/ 15°/ 30°/ 45°/ 60°/ 75°/ 90°	variable	0°/15°/30°/45°/60°/ 75°/90° and variable
Walkway application	yes	yes	yes	yes

Louvres with size 500 mm and 700 mm are also available for custom solutions.

TECHNICAL CHARACTERISTICS



BS 100 LOUVRE GRIP



BS 30 FRAME SYSTEM



BS 20 FRAME SYSTEM

Style variants			
Shape louvres	ellipse	z-shaped	curved
Size louvers	200 mm / 250 mm / 300 mm	90 mm wide x 60 mm high	80 mm / 140 mm wide
(Fixed) angle	0°/ 15° / 30°/ 45°	yes	30°
Walkway application	no	yes	no

